

PRODUCT DATA SHEET

Sikafloor® Antislip Agent

Anti-slip agent for Sikafloor® sealers

PRODUCT DESCRIPTION

Polypropylene-based additive to increase the slip resistance of Sikafloor® sealers.

USES

- Plastic granules to increase slip resistance.
- As an additive to various Sikafloor® EP and PU sealers.

CHARACTERISTICS / ADVANTAGES

- Optional system component for Sikafloor® sealers.
- Slip resistant.
- Abrasion resistant.
- Matting of glossy surfaces.

PRODUCT INFORMATION

Chemical Base	Fine-grained polypropylene granules
Packaging	Bag: 200 g
	Carton: 50 bags
Shelf Life	In unopened original container: 60 months from production date
Storage Conditions	Storage temperature between +5 °C and +30 °C. Store in a cool and dry place.
Appearance / Colour	White powder

APPLICATION INFORMATION

Consumption	2 - 4 % in Sikafloor® sealers
--------------------	-------------------------------

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

APPLICATION

Sikafloor® Antislip Agent is stirred into the selected Sikafloor® sealant before application.

For the description of the application of the sealer, see the corresponding product data sheet.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet
Sikafloor® Antislip Agent
December 2022, Version 02.01
020816010010000007

SikafloorAntislipAgent-en-GB-(12-2022)-2-1.pdf