MOTIP Hollow Section Wax 1 l

Technical Information



Beskytt hule områder i bilens karosseri mot rust med MOTIP Hollow Section Wax. Hulseksjonsvoks er motstandsdyktig mot vær og svake syrer og baser og har en utmerket rustforebygging. Hulprofilvoks har gode gjennomtrengende egenskaper.

Bestillingsnummer: 000034

Kvalitet og egenskaper

Skal påføres med en UBC spraypistol
Utmerket korrosjonsforebygging
Utmerket vedheft
Motstandsdyktig mot værpåvirkninger
Motstandsdyktig mot svake syrer og baser
Gode gjennomtrengende egenskaper

Fysiske og kjemiske data

Base: Voks
Kolourname: transparent white
Lukt: Karakteristisk
Effektivitet: 1,00 L – 6 -7 m²
Overflater: Hollow spaces in vehicle bodywork
Minimum arbeidstemperatur: 10 °C
Maksimal arbeidstemperatur: 25 °C
Flammepunkt: 29
Lagringsstabilitet: 5 y
Innhold: 1,00 L

Hvordan bruke

Les instruksjonene nøye før bruk.
Boksen skal ha romtemperatur. Beste behandlingstemperatur er mellom 10 og 25 °C.
Rist boksen godt før bruk. Arbeidstrykk 2,5 til 4 bar.
Påfør voksen sjenerøst i de hule områdene.
Rengjør spraypistolen med white spirit etter bruk

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as “special refuse”.

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of August 5, 2025 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim – info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega – info-nl@european-aerosols.com